

## Di Ethylene Glycol( DEG)

#	Characteristic	Test Method	Unit	Value
1	PURITY	ASTM E - 202	WT.%	99.8 MIN
2	MONOETHYLENE GLYCOL	ASTM E - 202	WT.%	0.05 MAX
3	TRIETHYLENE GLYCOL	ASTM E - 202	WT.%	0.05 MAX
4	WATER CONTENT	ASTM E - 202	WT.%	0.05 MAX
5	ACIDITY AS ACETIC ACID	ASTM D - 1613	PPM	50 MAX
6	ASH CONTENT	ASTM D - 254/A	PPM	50 MAX
7	SP. GR. (20/20 °C)	ASTM D - 891	.....	1.1175-1.1195
8	COLOR	ASTM D - 1209	Pt - Co	10 MAX
9	DISTILLATION @ 760 MM-Hg			
10	IBP	ASTM D - 1078	°C	242 MIN
11	DP	ASTM D - 1078	°C	250 MAX

Source: Arak Petrochemical Co.

Address: No. 1, Bank-e-Mellat Building, Alley No. 26, Mirzaye Shirazi Blvd, Shiraz, Iran

Tel: +98 21 8601 7283 , +98 71 3625 7570 - 1

Fax: +98 71 3625 3639

Website: [www.elsapaco.com](http://www.elsapaco.com)

Email: [info@elsapaco.com](mailto:info@elsapaco.com)